

## ACCESSORIES 1

### HIGH PRESSURE SOLENOID VALVES

Part Number	Specification	
95000	¼" SS NC Valve Body	Ideal for multiple zones and automatic control <ul style="list-style-type: none"> <li>• ¼" Normally closed 2/2 way valve</li> <li>• Corrosion proof</li> <li>• High temperature resistant</li> <li>• NEMA 4X coil</li> <li>• Stainless steel housing and piston</li> <li>• Up to 4 GPM and 1500 PSI</li> <li>• Inrush power consumption of 49VA</li> <li>• Holding power consumption of 28VA.</li> <li>• Outdoor Rated</li> </ul>
95002	24V AC Coil	
95003	110V AC Coil	
95004	220V AC Coil	



### ELECTRIC DRAIN VALVES

Part Number	Specification	
95001	1/4" SS NO Valve Body	Automatically drains line at shutdown. Reduces calcium and mineral buildup in line and nozzle heads. Normally open valve closed when energized. <ul style="list-style-type: none"> <li>• 1450 PSI Rated</li> <li>• Stainless Steel Body 1/4" FNPT ports</li> <li>• Coil continuous duty</li> <li>• Outdoor Rated</li> </ul>
95002	24V AC Coil	
95003	110V AC Coil	
95004	220V AC Coil	




### FLEXIBLE TUBING CUTTER

92710	Flexible Tubing Cutter	To be used for all nylon and poly tubing
-------	------------------------	--



### BRASS FITTINGS

92648	3/8" MNPT x 3/8" MNPT Nipple	Miscellaneous brass fittings used for pump and fog line multiple zone manifold assemblies
92649	1/2" MNPT x 1/2" MNPT Nipple	
93111	3/8" x 2" Nipple	
92717	3/8" Elbow	
93116	1/2" MNPT x 3/8" MNPT Reducing Nipple	
93118	1/4" FNPT Tee	
93119	3/8" FNPT Tee	
93185	3/8" MNPT x 1/4" MNPT Reducing Nipple	
93186	1/4" MNPT x 1/4" MNPT Nipple	
95025	3/8" FNPT Cross	



## ACCESSORIES 2

THERMAL RELIEF VALVE		
Part Number	Specification	
92629	1/2" MNPT	<p>Protects your pump against damaging heat if pump is left in bypass for extended periods.</p> <ul style="list-style-type: none"> <li>• Mounts on pump bypass loop</li> <li>• Brass Body 1/2 MNPT</li> <li>• Viton internal O ring seal</li> <li>• Discharge port 1/8" FNPT</li> <li>• Hose barb included</li> <li>• Relief temp 145 F</li> </ul>
LOW FLOW SAFETY SWITCH		
95070	1/2" FNPT	<ul style="list-style-type: none"> <li>• 1/4 GPM minimum flow requirement</li> <li>• Flow Switch contacts open with reduced flow</li> <li>• Used with contactor to control pump operation</li> <li>• Prevents pump damage due to no water or low water supply</li> </ul>
LOW WATER SAFETY SWITCH		
92509	1/4" FNPT	<p>Reverse action pressure switch contacts open on falling pressure. Protects your pump.</p> <ul style="list-style-type: none"> <li>• NEMA 1 enclosure</li> <li>• Two pole</li> <li>• 1 HP rated 115/230 volt</li> </ul>
PUMP PAD		
92715	Supports 1 thru 3 GPM pumps	High density polyethylene measures 24" x 24"
PUMP OIL		
93222	16oz.	Industrial Pump Oil
NOZZLE CLEANER		
10103	8oz.	<ul style="list-style-type: none"> <li>• Calcium &amp; Scale remover</li> <li>• Non-toxic</li> <li>• Bio-degradable</li> </ul>
92597	1 GALLON	
PRESSURE GUAGES 0-2K PSI		
93108	2" Panel Mount Gauge 1/8" MNPT.	Glycerin filled
93585	2 1/2" Bottom Mount Gauge 1/4" MNPT	
O-RINGS		
10252	Nozzle O-Ring	Black Buna rubber
92927	O-Ring Slip Lok - High Pressure	
STAINLESS BALL VALVES		
92631	1/4"x 1/4"	Two piece all stainless steel valve. ANSI 316 SS ball, stem and body 1000 PSI. WOG valve rating PTFE seats for long life. Valve can be locked in either open or closed position. Flows in either direction.

