

## PROMOTIONAL SERIES PUMP

The Medium Pressure Pump utilizes a brass rotary pump design and sealed bearings eliminating the need for oil lubrication and requires no maintenance. The Medium Pressure Pump produces up to 250 PSI while providing 1.1 gallons per minute. It is designed for light duty residential applications where price is the primary consideration and the Booster Pump does not provide sufficient flow.

- 1/2hp motor 50/60hz
- 250 PSI / 17 Bar
- 3/8" FNPT Connections
- Outdoor rated
- Brass rotary pump
- By-pass regulator valve
- Quiet operation
- Durable powder coat finish
- Solenoid valve
- 6 ft/1.8m power cord
- On/off switch



### 60Hz MODEL SPECIFICATIONS

Model Number	GPM	Nozzle Capacity**	Pressure PSI	HP Rating	Volts/Phase	Amp Rating	Dimensions L x H x W Inches	Weight lbs.
9075116	.75	24-48	250	.5	115/1	7.2	14 X 10 X 8	32
9075216	.75	24-48	250	.5	230/1	3.6	14 X 10 X 8	32

### 50Hz MODEL SPECIFICATIONS

Model Number	LPM	Nozzle Capacity**	Pressure BAR	HP Rating	Volts/Phase	Amp Rating	Dimensions L x H x W Inches	Weight lbs.
9023115	2	24-48	17	.5	115/1	7.2	14 X 10 X 8	32
9023215	2	24-48	17	.5	230/1	3.6	14 X 10 X 8	32

\*\*BASED ON .012 STD NOZZLE

### 15 NOZZLE PATIO KIT #94500

Model	Qty	Description
9075116	1	.75gpm med pressure pump 48 x 12 x 12 40lbs
10109	1	Calcium inhibitor filter
90425	1	25' roll of 1/4" HP nylon tubing brown
10128	1	10' roll of 3/8" low pressure tubing black
92705	1	Slip-lok brass hose adapter
94706	1	Slip-lok 1/4" end plug black plastic
93503	1	Medium pressure auto drain valve
94707	1	Slip-lok male adapter 1/4" slip-lok x 3/8" MNPT
93328	40	1/4" vinyl coated tubing clamp
93512	15	Brass/stainless .012" orifice nozzle
90430	14	30" straight lengths of 1/4" HP tubing brown
94630	16	Slip-lok T nozzle fitting for 1/4" tubing
92707	1	Slip-lok male adapter 3/8" slip-lok x 3/8" MNPT

